

## CT (RUBBER BASED) vs. ACRYLIC (WATER BASED) SEALOFLEX

This tip sheet is about the differences between Sealoflex CT™ (Rubber Based) and Sealoflex Water Based (Acrylic, or “Regular”) products. Solvent-based Sealoflex CT™ is a parallel system to the water based Sealoflex® System. The application process is the same for each – CT Pink™ / Fabric / CT Pink™ / two CT Top™ coats vs. Pink® / Fabric / Pink® / two Finish Coats™. The difference is that one is solvent-based and one is water-based; and that each serves different functions. And remember, you **cannot** mix and match the two systems.

### SIMILARITIES:

1. Both systems use **pink** as the **color** for the base and saturation coats.
2. Coverage rates are the same for either system.
3. The same fabrics are used for either system.

### DIFFERENCES:

1. Sealoflex CT™ is solvent based / Regular Sealoflex is water based.
2. Sealoflex CT™ is packaged in metal containers / Regular Sealoflex® is packaged in plastic containers.
3. Sealoflex CT™ can be used below grade for submerged conditions / Regular Sealoflex cannot be used below grade or for submerged conditions.
4. Sealoflex CT™ can be stored and applied with temperatures as low as 32 deg. / Regular Sealoflex® can be stored and applied with temperatures as low as 40 deg.
5. Sealoflex CT™ must be stirred / Regular Sealoflex® usually does not need stirring.
6. Sealoflex CT Top™ is available in white, gray or black only / Regular

Sealoflex Finish Coat™ is available in a variety of colors or can be custom matched to almost any color.

### USES FOR CT™:

1. Sealoflex CT™ for all conditions that do not have positive drainage.
2. Sealoflex CT™ for all conditions of ponding, pooling or standing water.
3. Sealoflex CT™ for all conditions that will bury the Sealoflex system.
4. Ponds, fountains, below grade foundation walls, under ceramic tile, gutters.

Please contact Bill Young at Sealoflex for additional information.

1-800-770-6466

[byoung@sealoflex.com](mailto:byoung@sealoflex.com)

[www.sealoflex.com](http://www.sealoflex.com)