

Enviroflex Primer EP1™ Adhesive and Blocking Primer

Description

Enviroflex Primer EP1™ is a low viscosity clear primer intended for adhesion promotion and blocking on difficult substrates.

Uses

Enviroflex Primer EP1™ is designed to accept top coats of Enviroflex™ Products, thus providing improved adhesion to the substrate. Typical applications are:

- Bituminous surfaces
- PVC Single Ply
- Treated and Untreated wood (to prevent bleed)

Advantages

Enviroflex EP1™ displays the following characteristics:

- Penetrates readily into the substrate
- Easy to apply
- Forms a sound substrate suitable for coating
- Dries quickly
- Chemical resistant

Coverage

Smooth surfaces:
Approximately 400 sq.ft./gal.

Granular surfaces:
Approximately 300 sq.ft./gal.

Instructions for Use

Surface Preparation

All surfaces must be clean, dry and free from oil, grease or loosely adhering particles.

Application

- Apply by brush, roller or airless spray equipment.
- Allow to dry until it becomes clear. Enviroflex™ can then be applied immediately.

Cleaning

Wash tools and equipment immediately after use with water.

Caution!

If concrete contains excessive moisture, see Product Data Sheets for Dampseal 101™ and Sealoment Plus™. Contact Sealoflex Technical Department.



Enviroflex Primer EP1™ goes on milky but dries clear,

Technical Data

| | |
|------------------------------------|---|
| Color: | Milky White; Dries Clear |
| Shelf Life and Storage Conditions: | 12 months if unopened & stored between 40°F & 90°F <i>Do Not Allow To Freeze</i> |
| Application Temperature: | +45°F to 105°F (Ambient) and +40°F to 130°F (Surface) |
| Density: | 8.5 lb./gal. |
| Packaging: | 1 gal and 5 gal plastic pails |

For this and/or related products, please refer to individual product data sheets, System Application Guides, Products MSDS, Primer Chart, Fabric Chart.

SEALOFLEX INC.

CORPORATE OFFICES

2520 Oscar Johnson Drive
Charleston, SC 29405
Tel: (843) 554-6466
(800) 770-6466
Fax: (843) 554-6458
Website: www.Sealoflex.com
E-mail: info@sealoflex.com

SALES OFFICE

CHARLESTON, SC
HAMBURG, GERMANY
CANTERBURY, KENT, U.K.

Sealoflex®

Waterproofing Systems

LIMITED WARRANTY

Sealoflex warrants its products to be free of manufacturing defects and that they will meet Sealoflex's current published physical properties when applied in accordance with Sealoflex's directions. There are no other warranties by Sealoflex of any nature whatsoever, expressed or implied, including any warranty of merchantability of fitness for a particular purpose in connection with this product. Sealoflex Inc. shall not be liable for damages of any sort, including remote or consequential damages, resulting from any claimed breach of any warranty whether expressed or implied, including any warranty of merchantability of fitness for a particular purpose or from any other cause whatsoever.

MARCH 2012

IMPORTANT NOTE: Always check our website, www.sealoflex.com to determine if the printed literature you are reading is the most current version available