

# Sealoflex Fabric Chart

<i>FABRIC BEING USED FOR...</i>	<i>4" and 6" JOINTING FABRIC</i>	<i>4" SEALOFLEX FABRIC</i>	<i>6" SEALOFLEX FABRIC</i>	<i>12" SEALOFLEX FABRIC</i>	<i>20" SEALOFLEX FABRIC</i>	<i>40" SEALOFLEX FABRIC</i>	<i>5' DECK FABRIC</i>
Copings				✓	✓		
Flashings			✓	✓			
Granular Modified			✓			✓	
GRR System			✓			✓	
Gutters			✓	✓	✓		
Metal Roofs (Joints and Laps only)	✓	✓	✓				
Parapet Walls				✓	✓	✓	
Plywood Decks			✓			✓	✓
Roof Panels (Insulation, Recovery Board)		✓	✓			✓	
Smooth Horizontal Concrete		✓				✓	
Smooth Modified			✓			✓	✓
Smooth Single Ply Recovery			✓			✓	✓
Textured or Rough Horizontal Surfaces			✓			✓	
Wall Joints and Cracks	✓						
Window and Door Openings	✓		✓				

- NEVER use Sealoflex Deck Fabric with Sealoflex CT Products.
- ONLY use Sealoflex Deck Fabric on smooth and flat surfaces.

**IMPORTANT NOTE:** Always check our website, [www.sealoflex.com](http://www.sealoflex.com) to determine if the printed literature you are reading is the most current version available.

For this and/or related products, please refer to individual product data sheets, System Application Guides, Products MSDS, Primer Chart, Fabric Chart.

# Sealoflex Fabrics

Type Fabric/Description	Advantages	Precautions/Instructions	Packaging
<p><b>Deck Fabric</b></p> <p>A 4 oz./sq.yd. knitted, polyester fiber fabric. It is used for smooth surfaces with the Sealoflex® Water Based System.</p>	<ul style="list-style-type: none"> <li>• Can be saturated from the top down without lay into a wet base layer</li> <li>• The 5' wide roll allows for minimal seams on trafficable decks, offering an aesthetically pleasing monolithic finish</li> </ul>	<ul style="list-style-type: none"> <li>• DO NOT use Sealoflex Deck Fabric on uneven surfaces, e.g., Granular Cap Sheet. Gravel Roofs, Rough Concrete, etc.</li> <li>• DO NOT use Sealoflex Deck Fabric with CT™ Products</li> </ul>	<ul style="list-style-type: none"> <li>• 5' x 100'</li> </ul>
<p><b>Jointing Fabric</b></p> <p>A knitted polyester fabric with a weight of 1.9 oz./sq.yd.</p>	<ul style="list-style-type: none"> <li>• Low Profile</li> <li>• In most cases, will be completely hidden when subsequent coats of product are applied.</li> <li>• Can be saturated from the top down without laying into a wet base layer.</li> </ul>	None	<ul style="list-style-type: none"> <li>• 4' x 300'</li> <li>• 6' x 300'</li> </ul>
<p><b>Sealoflex Fabric</b></p> <p>A 3.3 oz./sq.yd. polyester, non-woven, stitch-bonded and heat set fabric.</p>	<ul style="list-style-type: none"> <li>• Conforms readily to uneven surfaces</li> <li>• Easy to apply</li> <li>• Available in a variety of sizes</li> </ul>	<ul style="list-style-type: none"> <li>• When using Sealoflex Fabric, always lay the fabric into a generous coat of Sealoflex Pink®, allowing the wet product to saturate the fabric from below. Another coat of Sealoflex Pink® is ensure saturation from above.</li> <li>• When applying Sealoflex Fabric, to achieve an aesthetically pleasing finish, always apply with the “fluffy” side down.</li> </ul>	<ul style="list-style-type: none"> <li>• 4" x 300'</li> <li>• 6" x 300'</li> <li>• 12" x 300'</li> <li>• 20" x 300'</li> <li>• 40" x 100'</li> <li>• 40" x 324'</li> </ul>

