



GRACO SPRAYER GUIDE FOR SEALOFLEX PRODUCTS

Sealoflex Product	Unit	Gun	Tip	Hose Diameter & Length	Suggested Pressure	Mixing Instructions	Product Base
Coraflex™ (Fine Only)	Hopper or GTX 2000	Hopper or 3 ft Pole Gun	Med Tip	25 ft to 50 ft	65 PSI Fluid Air Pressure 35 PSI	Power mix	Water
CT Pink™	GMAX 5900 HD/Mark 5	Silver Gun	535 or >	3/8" Hose 50 ft up to 150 ft	2300 PSI or >	Power mix & strain material	Solvent
CT White™	GMAX 5900 HD/Mark 5	Silver Gun	535 or >	3/8" Hose 50 ft up to 150 ft	2300 PSI or >	Power mix & strain material	Solvent
CT FibreSeal™	GH 833	Sealwand by Sealoflex	665 or >	50 ft up to 300 ft	2800 PSI or >	Power mix	Solvent
Finish Coat™	GMAX 5900 HD/Mark 5	Silver Gun	623 or >	50 ft up to 300 ft	2800 PSI or >	Power mix & strain material	Water
Metal Etch Primer™	395 ST Ultra	Contractor 2	515	50 ft up to 300 ft	1800 to 2500 PSI	Power mix	Water
Sealcoat Elastic™	GMAX 5900 HD/Mark5	Blue Gun	517 or 519	50 ft up to 300 ft	2300 PSI or >	Power mix & strain material	Water
Sealcoat Elastic™	395 ST Ultra	Contractor 2	517	50 ft up to 300 ft	2500 PSI	Power mix & strain material	Water
Sealoflex Pink®	GMAX 5900 HD/Mark 5	Blue Gun	623 or >	50 ft up to 300 ft	2800 PSI or >	Power mix & strain material	Water
Wearcoat™	GMAX 5900 HD/Mark5	Blue Gun	517 or 519	50 ft up to 300 ft	2300 PSI or >	Power mix & strain material	Water

2520 Oscar Johnson Drive,
Charleston, SC 29405
843-554-6466 800-770-6466
www.sealoflex.com