

EP1 Primer

Adhesive and Stain Blocking Primer



Commercial Product Data Sheet

Description

EP1 Primer is a Water-Based, low viscosity, clear primer intended for adhesion promotion and stain blocking on various substrates.

Uses

- EPDM Black
- EPDM White
- Granular Modified/Smooth Modified
- Aged PVC
- Treated or Untreated Wood (to prevent tannin staining)

Advantages

- Penetrates into the substrate
- Easy to apply
- Dries quickly

Color

Milky white, dries clear

Coverage

200-400 sq. ft./gal., depending on porosity and texture of substrate.

Instructions for Use

Surface Preparation

All surfaces must be clean, dry and free from oil, grease or loosely adhering particles.

Application

Apply by brush, roller or sprayer. Allow to dry. Overcoat within 48 hours.

Cleaning

Wash tools and equipment with water immediately after use.



EP1 Primer™ goes on milky white, dries clear

EP1 Primer

Physical and Mechanical Properties

Property (as Manufactured)	Value
Color	Milky White; Dries Clear
Shelf Life and Storage Conditions	12 months if stored between +40°F & 90°F. <i>Do Not allow To Freeze.</i>
Density	8.5 lb./gal.
Drying Time	Approximately 20 minutes at 77°F, 50% RH
Application Temperature	+35°F to 105°F (Ambient) +35°F to 130°F (Surface)
Packaging	5 gallon pails

Ed. Jan 2016