

Sealoflex Fabric Chart

<i>FABRIC BEING USED FOR ...</i>	<i>4" and 6" JOINTING FABRIC™</i>	<i>4" SEALOFLEX FABRIC™</i>	<i>6" SEALOFLEX FABRIC™</i>	<i>12" SEALOFLEX FABRIC™</i>	<i>20" SEALOFLEX FABRIC™</i>	<i>40" SEALOFLEX FABRIC™</i>
Copings			√	√	√	√
Flashings			√	√	√	√
Granular Modified		√	√	√	√	√
GRR System		√	√	√	√	√
Gutters			√	√	√	√
Metal Roofs (Joints and Laps only)		√	√	√		
Parapet Walls				√	√	√
Plywood Decks			√	√	√	√
Roof Panels (Insulation, Recovery Board)			√	√	√	√
Smooth Horizontal Concrete			√	√	√	√
Smooth Modified			√	√	√	√
Smooth Single Ply Recovery			√	√	√	√
Wall Joints and Cracks	√					
Window and Door Openings	√	√	√	√		

IMPORTANT NOTE: Always check our website, www.sealoflex.com to determine if the printed literature you are reading is the most current version available.

For this and/or related products, please refer to individual product data sheets, System Application Guides, Products MSDS, Primer Chart, Fabric Chart.