



# Coraflex – all Colors

Safety Data Sheet 4013

Revision Date: 07/08/2016

Date of issue: 03/16/2016

Supersedes Date: 01/01/2005

Version: 1.0

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Coraflex – all Colors

### 1.2. Intended Use of the Product

**Use of the substance/mixture:** Crack bridging Elastic Stucco Finish

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

GAF  
1 Campus Drive  
Parsippany, NJ 07054 USA  
1-800-766-3411

**Emergency Number :** CHEMTREC [DAY OR NIGHT] 1-800-424-9300  
Outside USA and Canada: 1 703-741-5970

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US classification

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1 H317

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

: H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage.  
H402 - Harmful to aquatic life.  
H412 - Harmful to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US)

: P261 - Avoid breathing vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a poison center or doctor.  
P321 - Specific treatment (see section 4 on this SDS).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

# Coraflex – all Colors

Safety Data Sheet 4013

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Limestone	(CAS No) 1317-65-3	50 - 75	Not classified
Colorant 1	(CAS No) Proprietary†	<= 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Colorant 2	(CAS No) Proprietary†	<= 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Colorant 3	(CAS No) Proprietary†	<= 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Colorant 4	(CAS No) Proprietary†	<= 10	Not classified
Colorant 5	(CAS No) Proprietary†	<= 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Colorant 6	(CAS No) Proprietary†	<= 10	Not classified
Colorant 7	(CAS No) Proprietary†	<= 10	Eye Dam. 1, H318 Skin Sens. 1, H317
Colorant 8	(CAS No) Proprietary†	<= 10	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317
Colorant 9	(CAS No) Proprietary†	<= 10	Skin Irrit. 2, H315 Eye Dam. 1, H318
Colorant 10	(CAS No) Proprietary†	<= 10	Eye Irrit. 2B, H320
Colorant 11	(CAS No) Proprietary†	<= 10	Not classified
Colorant 12	(CAS No) Proprietary†	<= 10	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318
Colorant 13	(CAS No) Proprietary†	<= 10	Skin Irrit. 2, H315 Eye Dam. 1, H318
Colorant 14	(CAS No) Proprietary†	<= 10	Eye Dam. 1, H318
Colorant 15	(CAS No) Proprietary†	<= 10	Not classified
Colorant 16	(CAS No) Proprietary†	<= 10	Eye Dam. 1, H318 Skin Sens. 1, H317
Titanium dioxide	(CAS No) 13463-67-7	2 - 7	Not classified
Zinc oxide	(CAS No) 1314-13-2	0.5 - 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Surfactant 1	(CAS No) Proprietary	0.25 - 0.75	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Cosolvent 1	(CAS No) Proprietary	0.1 - 0.5	Not classified
Silica, amorphous	(CAS No) 7631-86-9	0.05 - 0.2	Not classified
Quartz	(CAS No) 14808-60-7	0.05 - 0.2	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Cosolvent 2	(CAS No) Proprietary	0.02 - 0.06	Flam. Liq. 4, H227
Cosolvent 3	(CAS No) Proprietary	0.02 - 0.06	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Cosolvent 4	(CAS No) Proprietary	< 0.005	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Antioxidant	(CAS No) Proprietary	< 0.002	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# Coraflex – all Colors

Safety Data Sheet 4013

Acrylic monomer 2	(CAS No) Proprietary	< = .0004	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402
-------------------	----------------------	-----------	---

Full text of H-phrases: see section 16

†These components are colorants that may be included on a customer specific basis up to 10% of the total weight of the mixture in any combination desired. The hazards in Section 2 associated with them are derived from each colorant being at 10% of the mixture.

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. In the event of an emergency, chemical identities and exact percentages of the proprietary ingredients may need to be disclosed to emergency personnel upon request.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Causes skin irritation. Causes serious eye damage. Skin sensitization.

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** None known.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire. Water spray, dry chemical, foam, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Under fire conditions closed containers may rupture or explode.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Remove containers from fire area if this can be done without risk. Do not breath fumes from fires or vapors from decomposition.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.

# Coraflex – all Colors

Safety Data Sheet 4013

## 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

## 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

## 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

## 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Take up large spills with pump or vacuum. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

## 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, and spray. Do not get in eyes, on skin, or on clothing.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Products:** Strong acids, strong bases, strong oxidizers. Anhydrides. Acid anhydrides.

**Storage Temperature:** 4 - 32 °C

### 7.3. Specific End Use(s)

Crack bridging Elastic Stucco Finish

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Acrylic monomer 2 (Proprietary)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	70 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	20 ppm
Cosolvent 1 (Proprietary)		
USA AIHA	WEEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Cosolvent 3 (Proprietary)		
USA ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol only)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
Cosolvent 2 (Proprietary)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA IDLH	US IDLH (ppm)	600 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>

# Coraflex – all Colors

Safety Data Sheet 4013

<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	100 ppm
<b>USA OSHA</b>	Limit value category (OSHA)	prevent or reduce skin absorption
<b>Titanium dioxide (13463-67-7)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
<b>Silica, amorphous (7631-86-9)</b>		
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	3000 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	20 mppcf (80mg/m <sup>3</sup> /%SiO <sub>2</sub> )
<b>Zinc oxide (1314-13-2)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (respirable fraction)
<b>USA ACGIH</b>	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (respirable fraction)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (dust and fume)
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
<b>USA NIOSH</b>	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (dust)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (fume) 15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>Limestone (1317-65-3)</b>		
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>Quartz (14808-60-7)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (respirable fraction)
<b>USA ACGIH</b>	ACGIH chemical category	A2 - Suspected Human Carcinogen
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> (respirable dust)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup> (respirable dust)
<b>USA OSHA</b>	OSHA PEL (STEL) (mg/m <sup>3</sup> )	250 mppcf/%SiO <sub>2</sub> +5, 10mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
<b>Cosolvent 4 (Proprietary)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	10 ppm (inhalable fraction and vapor)
<b>Antioxidant (Proprietary)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (inhalable fraction and vapor)
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>

## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles.



### Materials for Protective Clothing

: Chemically resistant materials and fabrics.

### Hand Protection

: Wear protective gloves.

### Eye Protection

: Chemical safety goggles.

### Skin and Body Protection

: Wear suitable protective clothing.

# Coraflex – all Colors

Safety Data Sheet 4013

<b>Respiratory Protection</b>	: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
<b>Environmental Exposure Controls</b>	: Avoid release to the environment.
<b>Other Information</b>	: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

<b>Physical State</b>	: Liquid
<b>Appearance</b>	: Various colors, Viscous liquid
<b>Odor</b>	: Mild Acrylic/Ammonia
<b>Odor Threshold</b>	: No data available
<b>pH</b>	: 8.5 - 9.5
<b>Evaporation Rate</b>	: < 1 (n-Butyl Acetate=1)
<b>Melting Point</b>	: No data available
<b>Freezing Point</b>	: ≈ 0 °C (32 °F)
<b>Boiling Point</b>	: ≈ 100 °C (212 °F)
<b>Flash Point</b>	: > 200 °F (> 93.33 °C) (PMCC)
<b>Auto-ignition Temperature</b>	: No data available
<b>Decomposition Temperature</b>	: No data available
<b>Flammability (solid, gas)</b>	: No data available
<b>Vapor Pressure</b>	: No data available
<b>Relative Vapor Density at 20 °C</b>	: Heavier than air
<b>Relative Density</b>	: No data available
<b>Specific Gravity</b>	: 1.80 - 1.92
<b>Specific gravity / density</b>	: 15 - 16 lb/gal
<b>Solubility</b>	: Miscible with water.
<b>Partition Coefficient: N-Octanol/Water</b>	: No data available
<b>Viscosity</b>	: 4000 - 6000 cPs

**9.2. Other Information** No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Anhydrides. Acid anhydrides.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Hydrocarbons. Acrylamide. Acrylates.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

**Acute Toxicity:** Not classified

<b>Acrylic monomer 2 (Proprietary)</b>	
<b>LD50 Oral Rat</b>	1060 mg/kg
<b>LD50 Dermal Rabbit</b>	500 - 1000 mg/kg
<b>LC50 Inhalation Rat</b>	7.1 mg/l/4h
<b>LC50 Inhalation Rat</b>	7.1 mg/l/4h
<b>ATE (Gases)</b>	4,500.00 ppmV/4h
<b>ATE (Dust/Mist)</b>	1.50 mg/l/4h
<b>Cosolvent 1 (Proprietary)</b>	
<b>LD50 Oral Rat</b>	20 g/kg
<b>LD50 Dermal Rabbit</b>	20800 mg/kg
<b>Cosolvent 3 (Proprietary)</b>	
<b>LD50 Dermal Rat</b>	10600 mg/kg

# Coraflex – all Colors

Safety Data Sheet 4013

<b>ATE (Oral)</b>	500.00 mg/kg body weight
<b>Cosolvent 2 (Proprietary)</b>	
<b>LD50 Oral Rat</b>	5400 µl/kg
<b>LD50 Dermal Rabbit</b>	9500 mg/kg
<b>Surfactant 1 (Proprietary)</b>	
<b>LD50 Oral Rat</b>	> 5000 mg/kg
<b>LD50 Dermal Rabbit</b>	> 2000 mg/kg
<b>LC50 Inhalation Rat</b>	> 5.2 mg/l/4h
<b>Titanium dioxide (13463-67-7)</b>	
<b>LD50 Oral Rat</b>	> 10000 mg/kg
<b>Silica, amorphous (7631-86-9)</b>	
<b>LD50 Oral Rat</b>	> 5000 mg/kg
<b>LD50 Dermal Rabbit</b>	> 2000 mg/kg
<b>LC50 Inhalation Rat</b>	> 2.2 mg/l (Exposure time: 1 h)
<b>Zinc oxide (1314-13-2)</b>	
<b>LD50 Oral Rat</b>	> 5000 mg/kg
<b>LD50 Dermal Rat</b>	> 2000 mg/kg
<b>Quartz (14808-60-7)</b>	
<b>LD50 Oral Rat</b>	> 5000 mg/kg
<b>LD50 Dermal Rat</b>	> 5000 mg/kg
<b>Cosolvent 4 (Proprietary)</b>	
<b>LD50 Oral Rat</b>	5660 mg/kg
<b>LD50 Dermal Rabbit</b>	2700 mg/kg
<b>Antioxidant (Proprietary)</b>	
<b>LD50 Oral Rat</b>	> 2930 mg/kg (Species: Sprague-Dawley)
<b>LD50 Dermal Rat</b>	> 2000 mg/kg
<b>Colorant 12 (Proprietary)</b>	
<b>ATE (Oral)</b>	500.00 mg/kg body weight

**Skin Corrosion/Irritation:** Causes skin irritation.

**pH:** 8.5 - 9.5

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**pH:** 8.5 - 9.5

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

<b>Titanium dioxide (13463-67-7)</b>	
<b>IARC group</b>	2B
<b>OSHA Hazard Communication Carcinogen List</b>	In OSHA Hazard Communication Carcinogen list.
<b>Silica, amorphous (7631-86-9)</b>	
<b>IARC group</b>	3
<b>Quartz (14808-60-7)</b>	
<b>IARC group</b>	1
<b>National Toxicology Program (NTP) Status</b>	Known Human Carcinogens.
<b>OSHA Hazard Communication Carcinogen List</b>	In OSHA Hazard Communication Carcinogen list.
<b>Antioxidant (Proprietary)</b>	
<b>IARC group</b>	3

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

# Coraflex – all Colors

Safety Data Sheet 4013

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** None known.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

<b>Acrylic monomer 2 (Proprietary)</b>	
LC50 Fish 1	85 mg/l (Exposure Time: 96 h - Species: Oncorhynchus mykiss [flow-through])
ErC50 (algae)	14 mg/l
NOEC chronic crustacea	53 mg/l
<b>Cosolvent 1 (Proprietary)</b>	
LC50 Fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	10000 mg/l (Exposure time: 24 h - Species: Daphnia magna)
LC 50 Fish 2	41 - 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>Cosolvent 3 (Proprietary)</b>	
LC50 Fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>Cosolvent 2 (Proprietary)</b>	
LC50 Fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Surfactant 1 (Proprietary)</b>	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>Silica, amorphous (7631-86-9)</b>	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
<b>Zinc oxide (1314-13-2)</b>	
LC50 Fish 1	780 µg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.122 mg/l
NOEC chronic fish	0.026 mg/l (Species: Jordanella floridae)
<b>Cosolvent 4 (Proprietary)</b>	
LC50 Fish 1	1300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Antioxidant (Proprietary)</b>	
EC50 Other Aquatic Organisms 2	0.43 mg/l (Exposure time: 72 h - Species: Desmodemus subspicatus)

### 12.2. Persistence and Degradability

<b>Coraflex White with Colorant</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.
<b>Cosolvent 2 (Proprietary)</b>	
Persistence and Degradability	Readily biodegradable.

### 12.3. Bioaccumulative Potential

<b>Coraflex White with Colorant</b>	
Bioaccumulative Potential	Not established.
<b>Acrylic monomer 2 (Proprietary)</b>	
Log Pow	0.93
<b>Cosolvent 1 (Proprietary)</b>	
BCF fish 1	< 1
Log Pow	-0.92
<b>Cosolvent 3 (Proprietary)</b>	
Log Pow	-1.93
<b>Cosolvent 2 (Proprietary)</b>	
Log Pow	-0.064 (at 20 °C)



# Coraflex – all Colors

Safety Data Sheet 4013

<b>Bioaccumulative Potential</b>	Not expected to bioaccumulate.
<b>Surfactant 1 (Proprietary)</b>	
<b>BCF fish 1</b>	61 - 159
<b>Silica, amorphous (7631-86-9)</b>	
<b>BCF fish 1</b>	(no bioaccumulation expected)
<b>Cosolvent 4 (Proprietary)</b>	
<b>BCF fish 1</b>	(no bioconcentration expected)
<b>Antioxidant (Proprietary)</b>	
<b>BCF fish 1</b>	230 - 2500
<b>Log Pow</b>	4.17

**12.4. Mobility in Soil** No additional information available

**12.5. Other Adverse Effects**

**Other Information** : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**13.1. Waste treatment methods**

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology – Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

**14.1. In Accordance with DOT** Not regulated for transport

**14.2. In Accordance with IMDG** Not regulated for transport

**14.3. In Accordance with IATA** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

**15.1 US Federal Regulations**

<b>Coraflex White with Colorant</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard
<b>Acrylic monomer 2 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cosolvent 1 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
<b>Cosolvent 3 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Cosolvent 2 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA
<b>Surfactant 1 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Titanium dioxide (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Silica, amorphous (7631-86-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# Coraflex – all Colors

Safety Data Sheet 4013

<b>Zinc oxide (1314-13-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Limestone (1317-65-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Quartz (14808-60-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cosolvent 4 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
<b>Antioxidant (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>15.2 US State Regulations</b>	
<b>Cosolvent 3 (Proprietary)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>Titanium dioxide (13463-67-7)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Quartz (14808-60-7)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Acrylic monomer 2 (Proprietary)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Cosolvent 1 (Proprietary)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Cosolvent 3 (Proprietary)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Cosolvent 2 (Proprietary)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Titanium dioxide (13463-67-7)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Silica, amorphous (7631-86-9)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Zinc oxide (1314-13-2)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	

# Coraflex – all Colors

Safety Data Sheet 4013

<b>Limestone (1317-65-3)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Quartz (14808-60-7)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Antioxidant (Proprietary)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 07/08/2016  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 2	Germ cell mutagenicity Category 2
Org. Perox. F	Organic Peroxide Category F
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
Skin Sens. 1B	Skin sensitization Category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid

# Coraflex – all Colors

Safety Data Sheet 4013

Comb. Dust	May form combustible dust concentrations in air
H242	Heating may cause a fire
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

## Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

## Revision Information

Conversion to GAF SDS.