



# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes Date: 01/01/2005

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Name:** Flashing Grade

### 1.2. Intended Use of the Product

**Use of the substance/mixture:** Flexible Waterproof Flashing Compound

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

GAF  
1 Campus Drive  
Parsippany, NJ 07054 USA  
1-800-766-3411

**Emergency Number :** CHEMTREC [DAY OR NIGHT] 1-800-424-9300  
Outside USA and Canada: 1 703-741-5970

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US classification

Skin Sens. 1 H317  
Aquatic Acute 2 H401  
Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



GHS07

##### Signal Word (GHS-US)

: Warning

##### Hazard Statements (GHS-US)

: H317 - May cause an allergic skin reaction.  
H401 - Toxic to aquatic life.  
H412 - Harmful to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US)

: P261 - Avoid breathing vapors, mist, or spray.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P321 - Specific treatment (see section 4 on this SDS).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Titanium dioxide	(CAS No) 13463-67-7	2 - 10	Not classified

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

Cellulose, 2-hydroxyethyl ether	(CAS No) 9004-62-0	< 5	Comb. Dust Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Zinc oxide	(CAS No) 1314-13-2	0.5 - 1.66	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Proprietary Cosolvent 1	(CAS No) Proprietary	0.2 - 1	Not classified
Proprietary Surfactant	(CAS No) Proprietary	0.05 - 0.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	0.1 - 0.4	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Silica, amorphous	(CAS No) 7631-86-9	0.05 - 0.4	Not classified
Proprietary Cosolvent	(CAS No) Proprietary	0.05 - 0.25	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Proprietary Surfactant 1	(CAS No) Proprietary	0.05 - 0.25	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
UV Absorber	(CAS No) Proprietary	< 0.1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Cellulose	(CAS No) 9004-34-6	<= 0.005	Comb. Dust

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. In the event of an emergency, chemical identities and exact percentages of the proprietary ingredients may need to be disclosed to emergency personnel upon request.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Skin sensitization.

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** None known.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire. Water spray, dry chemical, foam, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive. Containers may rupture when exposed to excessive heat.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Remove containers from fire area if this can be done without risk. Do not breathe fumes from fires or vapors from decomposition.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing.

#### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Take up large spills with pump or vacuum. Transfer spilled material to a suitable container for disposal. If spilled directly onto the ground, remove sufficient soil to ensure material is fully recovered. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, and spray.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool and well-ventilated place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Protect from freezing.

**Incompatible Products:** Strong acids, strong bases, strong oxidizers. Anhydrides. Acid anhydrides. Water reactive materials. Metal salts.

**Storage Temperature:** 4 - 32 °C

### 7.3. Specific End Use(s)

Flexible Waterproof Flashing Compound

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

<b>Proprietary Cosolvent (Proprietary)</b>		
<b>USA ACGIH</b>	ACGIH Ceiling (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup> (aerosol only)
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>Proprietary Cosolvent 1 (Proprietary)</b>		
<b>USA AIHA</b>	WEEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Titanium dioxide (13463-67-7)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
<b>Silica, amorphous (7631-86-9)</b>		
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	3000 mg/m <sup>3</sup>
<b>Zinc oxide (1314-13-2)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (respirable fraction)
<b>USA ACGIH</b>	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (respirable fraction)
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (dust and fume)
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
<b>USA NIOSH</b>	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (dust)
<b>USA IDLH</b>	US IDLH (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (fume) 15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>Cellulose (9004-34-6)</b>		
<b>USA ACGIH</b>	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)

## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles.



### Materials for Protective Clothing

: Chemically resistant materials and fabrics.

### Hand Protection

: Wear protective gloves.

### Eye Protection

: Chemical safety goggles.

### Skin and Body Protection

: Wear suitable protective clothing.

### Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

### Environmental Exposure Controls

: Avoid release to the environment.

### Other Information

: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: No data available
Odor	: Mild acrylic/ammonia
Odor Threshold	: No data available
pH	: 9 (≥ 9.5)

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

Evaporation Rate	: < 1 (n-Butyl Acetate=1)
Melting Point	: No data available
Freezing Point	: ≈ 0
Boiling Point	: ≈ 100
Flash Point	: > 200 °F (>93.33 °C) (PMCC)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: Heavier than air
Relative Density	: No data available
Specific Gravity	: 1.25 - 1.44
Specific gravity / density	: 10.4 - 12 lb/gal
Solubility	: Miscible with water.
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: 200,000 – 350,000 cPs

**9.2. Other Information** No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Anhydrides. Acid anhydrides. Water reactive materials. Metal salts.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Hydrocarbons. Acrylates. Methyl methacrylate. Organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

**Acute Toxicity:** Not classified

<b>Proprietary Cosolvent (Proprietary)</b>	
LD50 Dermal Rat	10600 mg/kg
ATE (Oral)	500.00 mg/kg body weight
<b>Proprietary Surfactant 1 (Proprietary)</b>	
LD50 Dermal Rat	> 2000 mg/kg
<b>Proprietary Surfactant (Proprietary)</b>	
LD50 Oral Rat	1310 mg/kg HSDB
LD50 Dermal Rabbit	1780 ml/kg
<b>Proprietary Cosolvent 1 (Proprietary)</b>	
LD50 Oral Rat	20 g/kg
LD50 Dermal Rabbit	20800 mg/kg
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h
<b>Titanium dioxide (13463-67-7)</b>	
LD50 Oral Rat	> 10000 mg/kg
<b>Silica, amorphous (7631-86-9)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 2.2 mg/l (Exposure time: 1 h)
<b>Zinc oxide (1314-13-2)</b>	
LD50 Oral Rat	> 5000 mg/kg

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

LD50 Dermal Rat	> 2000 mg/kg
<b>Cellulose (9004-34-6)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5800 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>UV Absorber (Proprietary)</b>	
LD50 Oral Rat	550 mg/kg
LD50 Dermal Rat	690 mg/kg
LD50 Dermal Rabbit	690 mg/kg
LC50 Inhalation Rat	0.586 mg/l/4h
ATE (Gases)	700.00 ppmV/4h
ATE (Vapors)	3.00 mg/l/4h
ATE (Dust/Mist)	0.50 mg/l/4h

**Skin Corrosion/Irritation:** Not classified

**pH:** 9 (≥ 9.5)

**Serious Eye Damage/Irritation:** Not classified

**pH:** 9 (≥ 9.5)

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
<b>Silica, amorphous (7631-86-9)</b>	
IARC group	3

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** None known.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

<b>Proprietary Cosolvent (Proprietary)</b>	
LC50 Fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>Proprietary Surfactant 1 (Proprietary)</b>	
LC50 Fish 1	42 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	91 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Proprietary Surfactant (Proprietary)</b>	
EC50 Daphnia 1	1.821 mg/l
<b>Proprietary Cosolvent 1 (Proprietary)</b>	
LC50 Fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	10000 mg/l (Exposure time: 24 h - Species: Daphnia magna)
LC 50 Fish 2	41 - 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC 50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

<b>Silica, amorphous (7631-86-9)</b>	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
<b>Zinc oxide (1314-13-2)</b>	
LC50 Fish 1	780 µg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.122 mg/l
NOEC chronic fish	0.026 mg/l (Species: Jordanella floridae)
<b>UV Absorber (Proprietary)</b>	
LC50 Fish 1	0.047 mg/kg (Exposure Time: 96 h - Species: Oncorhynchus mykiss [Flow-through])
LC 50 Fish 2	0.05 ppm Exposure Time: 96 h - Species: Oncorhynchus mykiss [static]
NOEC chronic fish	< 0.05
NOEC chronic algae	< 0.011 (Test Duration: 120 h - Species: Selenastrum capricornutum [static])

## 12.2. Persistence and Degradability

<b>Flashing Grade</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.

## 12.3. Bioaccumulative Potential

<b>Flashing Grade</b>	
Bioaccumulative Potential	Not established.
<b>Proprietary Cosolvent (Proprietary)</b>	
Log Pow	-1.93
<b>Proprietary Cosolvent 1 (Proprietary)</b>	
BCF fish 1	< 1
Log Pow	-0.92
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
BCF fish 1	61 - 159
<b>Silica, amorphous (7631-86-9)</b>	
BCF fish 1	(no bioaccumulation expected)

12.4. Mobility in Soil No additional information available

## 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Sewage Disposal Recommendations:** Do not empty into drains; dispose of this material and its container in a safe way.

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology – Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

<b>Flashing Grade</b>	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
<b>Proprietary Cosolvent (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
SARA Section 313 - Emission Reporting	1.0 %

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

<b>Proprietary Surfactant 1 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Proprietary Surfactant (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule
<b>Proprietary Cosolvent 1 (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Titanium dioxide (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Silica, amorphous (7631-86-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Zinc oxide (1314-13-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cellulose, 2-hydroxyethyl ether (9004-62-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cellulose (9004-34-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>UV Absorber (Proprietary)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

## 15.2 US State Regulations

<b>Proprietary Cosolvent (Proprietary)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>Titanium dioxide (13463-67-7)</b>	
<b>U.S. - California - Proposition 65 - Carcinogens List</b>	WARNING: This product contains chemicals known to the State of California to cause cancer.
<b>Proprietary Cosolvent (Proprietary)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Proprietary Cosolvent 1 (Proprietary)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Titanium dioxide (13463-67-7)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Silica, amorphous (7631-86-9)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Zinc oxide (1314-13-2)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List	



# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

## Cellulose (9004-34-6)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 07/28/2016

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
Skin Sens. 1B	Skin sensitization Category 1B
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
Comb. Dust	May form combustible dust concentrations in air
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

# Flashing Grade

Safety Data Sheet 4043

Revision Date: 07/28/2016

Date of issue: 04/06/2016

Supersedes

H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

## Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

## Revision Information

Conversion to GAF SDS.